


Alem Track Lights

Technical Data Sheet

ITEM SKU#: 662187489100



Product Code : IK-RALEMTL-20W-50K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	2018.78lm
Power	20W
Efficacy	140lm/w
ССТ	5000K
CRI	>90
Beam Angle	15°
Light Distribution	Spot
LED Type	СОВ
LED Light Source	Bridgelux V13
Start Time	Instant
Driver	IK-LKAD029DC-05242
Operating Position	Swiveling Type
Dimming	0-10V
Construction	Track
Mounting Type	Track Light Structure
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	4-7/8"
Height	7"
Diameter	2-3/4"
Application Area	Indoor Applications

Technical Data

IES File Link 🛃

Installation Instructions Link 🕹

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

Spot

ft

3.0

9.0

15.0

15° Medium

ø ft

0.72 3.0

2.15 9.0

3.58 15.0 <mark>24°</mark> Ø Flood

1.41

4.22

7.04

ft

3.0

9.0

15.0

38°

ø ft

2.03

6.09

10.15 15.0

Wide Flood 60

3.0

9.0

Ø

3.15

<mark>9.</mark>45

15.75