


Alem Track Lights

ITEM SKU#: 662187489605













Product Code: IK-RALEMTL-20W-50K-WH-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz		
Lumen Output	2008.97lm		
Power	20W		
Efficacy	140lm/w		
ССТ	5000K		
CRI	>90		
Beam Angle	60°		
Light Distribution	Wide flood		
LED Type	COB		
LED Light Source	Bridgelux V13		
Start Time	Instant		
Driver	IK-LKAD029DC-05242		
Operating Position	Swiveling Type		
Dimming	0-10V		
Construction	Track		
Mounting Type	Track Light Structure		
Heads	Single Head		
Body Material	Aluminium Die cast		
Finish	White		
Length	4-7/8"		
Height	7"		
Diameter	2-3/4"		
Application Area	Indoor Applications		

3eam	Sprea	d (Options))				
Spot	15°	Medium	24°	Flood	38°	Wide Flo	od 60°
ft	Ø	ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75
	Spot ft 3.0 9.0	Spot 15° ft Ø 3.0 0.72 9.0 2.15	Spot 15° Medium ft Ø ft 3.0 0.72 3.0 9.0 2.15 9.0	ft Ø ft Ø 3.0 0.72 3.0 1.41 9.0 2.15 9.0 4.22	Spot 15* Medium 24* Flood ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 9.0 2.15 9.0 4.22 9.0	Spot 15° Medium 24° Flood 38° ft Ø ft Ø ft Ø 3.0 0.72 3.0 1.41 3.0 2.03 9.0 2.15 9.0 4.22 9.0 6.09	Spot 15° Medium 24° Flood 38° Wide Flo ft Ø ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 2.03 3.0 9.0 2.15 9.0 4.22 9.0 6.09 9.0

Alem is a technologically advanced LED track light with incorporated electronic gear and chip on board.It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminium for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link ±

Installation Instructions Link 🕹

