


Bolide Track Lights















Product Code: IK-RBOLIDETL-30W-27K-BL-90C-38D

Voltage	100 - 277 V AC, 50-60 Hz					
Lumen Output	2584.09lm					
Power	30W					
Efficacy	140lm/w					
CCT	2700K					
CRI	>90					
Beam Angle	38°					
Light Distribution	Flood					
LED Type	COB					
LED Light Source	Osram SOLERIQ S 19					
Start Time	Instant					
Driver	Stand Alone (included)					
Operating Position	Swiveling Type					
Dimming	Triac Dimming					
Construction	Track					
Mounting Type	Track Light Structure					
Heads	Single Head					
Finish	Black					
Length	4-5/8"					
Height	7-5/8"					
Diameter	3-1/2"					
Cut Out	7-3/8"					
Width (W)	7-3/8"					
Application Area	Indoor Applications					

Beam Spread (Options)											
Spot		15°	Mediu	m	25°	Flood		36°	Wide	Flood	60°
ft		Ø	ft		Ø	ft		Ø	ft		Ø
3.0		0.72	3.0		1.41	3.0		2.03	3.0		3.15
9.0		2.15	9.0		4.22	9.0		6.09	9.0		9.45
15.0		2.50	15.0		704	15.0		1015	15.0		15.75

Bolide is a technologically advanced LED track light with incorporated electronic gear and chip on board. It also has a high-quality reflector with three different beam spreads. Moreover, the lamp housing of die-cast aluminum for optimal cooling allows the fixture to last longer than its traditional counterparts.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

