

Nova Down Lights

ITEM SKU#: 662187496528



CE





Product Co	ct Code : IK-RNOVADL-20W-27K-WH-90C-36D	
Voltage	100 - 277 V AC, 50-60 Hz	

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1600lm
Power	20W
Efficacy	80lm/w
ССТ	2700K
CRI	>90
Beam Angle	36°
Light Distribution	Flood
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type, 360D
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Height	4-7/8"
Diameter	5-1/4"
Cut Out	4-3/4"
Optics	Darklight Technology Black, Silver
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options) Spot 15" Medium 24" Flood ft Ø ft Ø ft Ø ft 3.0 0.72 3.0 1.41 3.0 3.0 1.41 3.0

9.0

2.15

3.58 15.0

9.0

15.0

4.22

7.04

9.0

15.0

Ø

2.03

6.09

10.15

Nova, a round shaped LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. The specular darklight reflector in this store light allows outstanding visual comfort to the visitors so that they are able to explore the merchandise at ease.



retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.