

Odin Down Lights

ITEM SKU#: 662187498058



COB LED


Product Code : IK-RODINDL-55W-27K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	7200lm
Power	55W
Efficacy	140lm/w
ССТ	2700K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type, 360D
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Double Head
Body Material	Aluminium Die cast
Finish	White
Length	9-7/8"
Height	4-7/8"
Cut Out	9"x4-7/8"
Optics	Darklight Technology Black, Silver
Width (W)	5-1/2"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)

Spot	15°	Medium	24°	Flood	36°
ft	Ø	ft	Ø	ft	Ø
3.0	0.72	3.0	1.41	3.0	2.03
9.0	2.15	9.0	4.22	9.0	6.09
15.0	3.58	15.0	7.04	15. <mark>0</mark>	10.15

Create the desired lighting effect in your stores with IKIO's Odin, a twin square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. These properties of the luminaire contribute to its effective functioning for a longer time period. Moreover, available in multiple wattages, color temperatures, finishes, and beam angles, this luminaire offers greater flexibility in its application.



DIMMABLE

IP20

🖲 Ikio

© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.