


Olivio Down Lights















Product Code: IK-ROLIVIODL-8W-27K-BL-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz					
Lumen Output	644.85lm					
Power	8W					
Efficacy	140lm/w					
CCT	2700K					
CRI	>90					
Beam Angle	15°					
Light Distribution	Spot					
LED Type	COB					
LED Light Source	Osram SOLERIQ S 19					
Start Time	Instant					
Driver	Stand Alone (included)					
Operating Position	Non - Swiveling Type					
Dimming	On-Off / Triac / 0-10 V					
Dimming Construction	On-Off / Triac / 0-10 V Round					
-						
Construction	Round					
Construction Mounting Type	Round Recessed					
Construction Mounting Type Heads	Round Recessed Single Head					
Construction Mounting Type Heads Body Material	Round Recessed Single Head Aluminium Die cast					
Construction Mounting Type Heads Body Material Finish	Round Recessed Single Head Aluminium Die cast Black					
Construction Mounting Type Heads Body Material Finish Height	Round Recessed Single Head Aluminium Die cast Black 4"					
Construction Mounting Type Heads Body Material Finish Height Diameter	Round Recessed Single Head Aluminium Die cast Black 4" 6-1/2"					

Beam Spread (Options)								
Spot	15°	Medium	24°	Flood	38°	Wide Fl	ood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	
9.0	2.15	9.0	4.22	9.0	6.09	9.0	9.45	
15.0	3.58	15.0	7.04	15.0	10.15	15.0	15.75	

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

