


Olivio Down Lights















Product Code: IK-ROLIVIODL-8W-40K-BL-90C-24D

| Voltage | 100 - 277 V AC, 50-60 Hz | | | | |
|--|--|--|--|--|--|
| Lumen Output | 750.58lm | | | | |
| Power | 8W | | | | |
| Efficacy | 140lm/w | | | | |
| CCT | 4000K | | | | |
| CRI | >90 | | | | |
| Beam Angle | 24° | | | | |
| Light Distribution | Medium | | | | |
| LED Type | COB | | | | |
| LED Light Source | Osram SOLERIQ S 19 | | | | |
| Start Time | Instant | | | | |
| Driver | Stand Alone (included) | | | | |
| Operating Position | Non - Swiveling Type | | | | |
| Dimming | On-Off / Triac / 0-10 V | | | | |
| Construction | Round | | | | |
| | | | | | |
| Mounting Type | Recessed | | | | |
| Mounting Type Heads | Recessed Single Head | | | | |
| · · · · | | | | | |
| Heads | Single Head | | | | |
| Heads Body Material | Single Head Aluminium Die cast | | | | |
| Heads Body Material Finish | Single Head Aluminium Die cast Black | | | | |
| Heads Body Material Finish Height | Single Head Aluminium Die cast Black 4" | | | | |
| Heads Body Material Finish Height Diameter | Single Head Aluminium Die cast Black 4" 6-1/2" | | | | |

| Beam Spread (Options) | | | | | | | | |
|-----------------------|------|--------|------|-------|-------|---------|---------|--|
| Spot | 15° | Medium | 24° | Flood | 38° | Wide Fl | ood 60° | |
| ft | Ø | ft | Ø | ft | Ø | ft | Ø | |
| 3.0 | 0.72 | 3.0 | 1.41 | 3.0 | 2.03 | 3.0 | 3.15 | |
| 9.0 | 2.15 | 9.0 | 4.22 | 9.0 | 6.09 | 9.0 | 9.45 | |
| 15.0 | 3.58 | 15.0 | 7.04 | 15.0 | 10.15 | 15.0 | 15.75 | |
| | | | | | | | | |

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

