


Olivio Down Lights

ITEM SKU#: 662187499048













Product Code: IK-ROLIVIODL-8W-40K-WH-90C-24D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	750.58lm
Power	8W
Efficacy	140lm/w
CCT	4000K
CRI	>90
Beam Angle	24°
Light Distribution	Medium
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Dimming Construction	On-Off / Triac / 0-10 V Round
-	
Construction	Round
Construction Mounting Type	Round Recessed
Construction Mounting Type Heads	Round Recessed Single Head
Construction Mounting Type Heads Body Material	Round Recessed Single Head Aluminium Die cast
Construction Mounting Type Heads Body Material Finish	Round Recessed Single Head Aluminium Die cast White
Construction Mounting Type Heads Body Material Finish Height	Round Recessed Single Head Aluminium Die cast White 4"
Construction Mounting Type Heads Body Material Finish Height Diameter	Round Recessed Single Head Aluminium Die cast White 4" 6-1/2"

Beam Spread (Options)								
15°	Medium	24°	Flood	38°	Wide Fl	ood 60°		
Ø	ft	Ø	ft	Ø	ft	Ø		
0.72	3.0	1.41	3.0	2.03	3.0	3.15		
2.15	9.0	4.22	9.0	6.09	9.0	9.45		
3.58	15.0	7.04	15.0	10.15	15.0	15.75		
	0.72 2.15	15° Medium Ø ft 0.72 3.0 2.15 9.0	15° Medium 24° Ø ft Ø 0.72 3.0 1.41 2.15 9.0 4.22	15° Medium 24° Flood Ø ft Ø ft 0.72 3.0 1.41 3.0 2.15 9.0 4.22 9.0	15° Medium 24° Flood 38°	15° Medium 24° Flood 38° Wide Flood 07° 07° 30° 1.41 30° 2.03 30° 2.15 9.0 4.22 9.0 6.09 9.0		

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link <u>⊀</u>

Installation Instructions Link 🕹

