


Olivio Down Lights















Product Code: IK-ROLIVIODL-15W-35K-WH-90C-15D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1350.72lm
Power	15W
Efficacy	140lm/w
CCT	3500K
CRI	>90
Beam Angle	15°
Light Distribution	Spot
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Round
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Height	4-7/8"
Diameter	6-1/2"
Cut Out	3"
Optics	Darklight Technology Black, Silver
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)								
15°	Medium	24°	Flood	38°	Wide Fl	ood 60°		
Ø	ft	Ø	ft	Ø	ft	Ø		
0.72	3.0	1.41	3.0	2.03	3.0	3.15		
2.15	9.0	4.22	9.0	6.09	9.0	9.45		
3.58	15.0	7.04	15.0	10.15	15.0	15.75		
	0.72 2.15	15° Medium Ø ft 0.72 3.0 2.15 9.0	15° Medium 24° Ø ft Ø 0.72 3.0 1.41 2.15 9.0 4.22	15° Medium 24° Flood Ø ft Ø ft 0.72 3.0 1.41 3.0 2.15 9.0 4.22 9.0	15° Medium 24° Flood 38°	15° Medium 24° Flood 38° Wide Flood 07° 07° 30° 1.41 30° 2.03 30° 2.15 9.0 4.22 9.0 6.09 9.0		

Olivio, a round LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid /global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Technical Data

IES File Link ±

Installation Instructions Link 🕹

