


**Thiea Down Lights** 

## ITEM SKU#: 662187500294







Lumen Output	723.30111
Power	8W
Efficacy	140lm/w
ССТ	3500K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	Black
Length	2-7/8"
Height	4"
Cut Out	3"x3"

## Product Code : IK-RTHEIADL-8W-35K-BL-90C-60D

100 - 277 V AC, 50-60 Hz

729.96lm

Voltage

Optics

9.0

15.0

Width (W)

Application Area

2.15 9.0

3.58 15.0

Lumen Output

Beam	n Sprea	d (Options	5)					
Spot	15°	Medium	24°	Flood	38°	Wide	Flood 60°	
ft	Ø	ft	Ø	ft	Ø	ft	Ø	cast with high housing and o
3.0	0.72	3.0	1.41	3.0	2.03	3.0	3.15	power grid /gl

6.09 9.0

10.15

15.0

2-7/8"

4.22 9.0

7.04

15.0

Darklight Technology Black, Silver

<mark>9.</mark>45

15.75

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid / global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

## Technical Data

IES File Link 🕹

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com

© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.

