


## Thiea Down Lights

ITEM SKU#: 662187500744













## Product Code: IK-RTHEIADL-15W-30K-WH-90C-38D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1284.7lm
Power	15W
Efficacy	140lm/w
CCT	3000K
CRI	>90
Beam Angle	38°
Light Distribution	Flood
LED Type	СОВ
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Mounting Type	Recessed
Heads	Single Head
Body Material	Aluminium Die cast
Finish	White
Length	3-3/4"
Height	5-1/8"
Cut Out	3-7/8"
Optics	Darklight Technology Black, Silver
Width (W)	3-3/4"
Application Area	Guest Room, Corridor, Restaurant, Meeting Room Club, Hall, Hotel Entrance

Beam Spread (Options)													
Spot		15°	Mediur	m	24°		Flood		38°	Wie	de	Flood	60°
ft		Ø	ft		Ø		ft		Ø	ft			Ø
3.0		0.72	3.0		1.41		3.0		2.03	3.	0		3.15
9.0		2.15	9.0		4.22		9.0		6.09	9.	0		9.45
15.0		3.58	15.0		7.04		15.0		10.15	15	.0		15.75

Theia, a square LED downlight made of aluminum die cast with high quality powder coated luminaire housing and optimum heat sink. Specular reflector & power grid (global connectors available with isolated LED Driver using Ultra bright OSRAM COB.

## Technical Data

