


Flare Down Lights















Product Code: IK-RFLAREDL-20W-35K-WH-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1800lm
Power	20W
Efficacy	90lm/w
CCT	3500K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Non - Swiveling Type
Dimming	On-Off / Triac / 0-10 V
Construction	Sqaure
Construction Mounting Type	Sqaure Recessed
	•
Mounting Type	Recessed
Mounting Type Heads	Recessed Single Head
Mounting Type Heads Finish	Recessed Single Head White
Mounting Type Heads Finish Height	Recessed Single Head White 3"
Mounting Type Heads Finish Height Diameter	Recessed Single Head White 3" 5"x5"
Mounting Type Heads Finish Height Diameter Cut Out	Recessed Single Head White 3" 5"x5" 4-3/8"x4-3/8"

Beam Spread (Opti	on
-------------------	----



Flare downlight is a square shaped fixture, that illuminates a store in the most effective manner without being obtrusive. The smart engineering of the luminaire with specular reflector & power grid/global connectors along with high voltage standing in-house LED driver makes it an ideal choice for lighting your stores.

