

Flare Down Lights

ITEM SKU#: 662187493480



Product Code : IK-RFLAREDL-40W-35K-BL-90C-60D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	3600lm
Power	40W
Efficacy	90lm/w
ССТ	3500K
CRI	>90
Beam Angle	60°
Light Distribution	Wide flood
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Billion	
Operating Position	Non - Swiveling Type
Operating Position	Non - Swiveling Type
Operating Position Dimming	Non - Swiveling Type On-Off / Triac / 0-10 V
Operating Position Dimming Construction	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure
Operating Position Dimming Construction Mounting Type	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure Recessed
Operating Position Dimming Construction Mounting Type Heads	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure Recessed Single Head
Operating Position Dimming Construction Mounting Type Heads Finish	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure Recessed Single Head Black
Operating Position Dimming Construction Mounting Type Heads Finish Height	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure Recessed Single Head Black 3"
Operating Position Dimming Construction Mounting Type Heads Finish Height Diameter	Non - Swiveling Type On-Off / Triac / 0-10 V Sqaure Recessed Single Head Black 3" 8-1/4"x8-1/4"

Beam Spread (Option)



Flare downlight is a square shaped fixture, that illuminates a store in the most effective manner without being obtrusive. The smart engineering of the luminaire with specular reflector & power grid/ global connectors along with high voltage standing in-house LED driver makes it an ideal choice for lighting your stores.

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com



© IKIO LED LIGHTING 2025. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.