


Mica Pendant Lights

ITEM SKU#: 662187507064













Product Code: IK-RMicaPL-20W-50K-WH-90C-45D

Voltage 100 - 277 V AC, 50-60 Hz Lumen Output 1900lm Power 20W CCT 5000K CRI >90 Beam Angle 45° Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8" Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance		
Power 20W CCT 5000K CRI >90 Beam Angle 45° Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/8" Optics Reflective Cup Structure Width (W) 4-3/8"	Voltage	100 - 277 V AC, 50-60 Hz
CCT 5000K CRI >90 Beam Angle 45° Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Lumen Output	1900lm
CRI >90 Beam Angle 45° Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Power	20W
Beam Angle 45° Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/8" Optics Reflective Cup Structure Width (W) 4-3/8"	CCT	5000K
Light Distribution Flood LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	CRI	>90
LED Light Source Osram SOLERIQ S 19 Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Beam Angle	45°
Start Time Instant Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Light Distribution	Flood
Driver Stand Alone (included) Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	LED Light Source	Osram SOLERIQ S 19
Operating Position No Swiveling Type Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Start Time	Instant
Dimming Triac Dimming / 0-10 V Dimming Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Driver	Stand Alone (included)
Heads Single Head Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Operating Position	No Swiveling Type
Finish White Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Dimming	Triac Dimming / 0-10 V Dimming
Length 4-3/8" Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Heads	Single Head
Height 4-3/4" Optics Reflective Cup Structure Width (W) 4-3/8"	Finish	White
Optics Reflective Cup Structure Width (W) 4-3/8"	Length	4-3/8"
Width (W) 4-3/8"	Height	4-3/4"
· ·	Optics	Reflective Cup Structure
Application Area Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance	Width (W)	4-3/8"
	Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

Beam Spread (Options)											
Spot		15°	Мє	ediu	m	30	۰	Flood		45°	
ft		Ø	ft			Ø		ft		Ø	
3.0	<u> </u>	0.72	3	.0		1.41		3.0		2.03	
9.0		2.15	9	.0		4.22		9.0		6.09	
15.0	_ :	3.58	15	5.0		7.04		15.0		10.15	

Mica is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with wide beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

