


## **Remus Pendant Lights**

## ITEM SKU#: 662187507248



CE

COB LED

## Product Code : IK-RRemusPL-20W-27K-WH-90C-11D

Voltage	100 - 277 V AC, 50-60 Hz
Lumen Output	1800lm
Power	20W
ССТ	2700K
CRI	>90
Beam Angle	11°
Light Distribution	Spot
LED Light Source	Osram SOLERIQ S 19
Start Time	Instant
Driver	Stand Alone (included)
Operating Position	Swiveling Type
Dimming	Triac Dimming
Heads	Single Head
Finish	White
Height	6-5/8"
Diameter	3-1/8"
Application Area	Guest Room, Restaurant, Meeting Room, Club, Hall, Hotel Entrance

## Beam Spread (Options)

Spot		11°	Mediur	n	24°	Flood		30°		
ft		Ø	ft		Ø	ft		Ø		
3.0		0.72	3.0		1.41	3.0		2.03		
9.0		2.15	9.0		4.22	9.0		6.09		
15.0		3.58	15.0		7.04	15 <mark>.0</mark>		10.15		
	ft 3.0 9.0	ft 3.0 9.0	Spot 11°   ft Ø   3.0 0.72   9.0 2.15	Spot 11° Mediur   ft Ø ft   3.0 0.72 3.0   9.0 2.15 9.0	Spot 11° Medium   ft Ø ft   3.0 0.72 3.0   9.0 2.15 9.0	Spot 11° Medium 24°   ft Ø ft Ø   3.0 0.72 3.0 1.41   9.0 2.15 9.0 4.22	Spot 11* Medium 24* Flood   ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0   9.0 2.15 9.0 4.22 9.0	Spot 11° Medium 24° Flood   ft Ø ft Ø ft   3.0 0.72 3.0 1.41 3.0   9.0 2.15 9.0 4.22 9.0		

Remus is a technologically advanced LED Pendant Light that incorporates electronic gear and a high-quality lens with different beam spread. While commonly used as task light, the unique and state-of-the-art design of this luminaire also enhances the overall aesthetics of your store.

retail@ikioledlighting.com I +1 844-533-4546 I www.retail.ikioledlighting.com



© IKIO LED LIGHTING 2024. All Rights Reserved. Products and technologies in this document may be covered by one or more Patents Pending.

٥

IP20

DIMMABLE

The product images shown are for illustration purposes only and may not be an exact representation of the product. Specifications subject to change without notice.